



THE FIRST INTEGRATED SCREEN BOOM BARRIER INSTANT IMPACT MESSAGING AT FIRST GLANCE



Adaptable to all LBA barriers	The First Fully built in screen. Perfect sightline	21.5 inch, iK8 high quality screen	Customisation of content using intuitive media player	Durable screen with scratch and UV protection
--------------------------------------	--	------------------------------------	---	---

STANDARD CHARACTERISTICS

- Speed:** Variable from 0.8 seconds
- Continuous and intensive operation:** 15,000 cycles/day
- Boom:** Ø 85 mm articulated or straight oval lateral aluminium, length up to 3.80 m
- Geared motor:** Three-phase / 230 V single-phase power supply
- Spring:** Compression-monitored counterbalance spring
- Housing:** Cataphoresis treated steel sheet with a Ronis 405 lock + Standard RAL 5015
- Top cover:** 2 mm thick aluminium sheet with RAL 9010 paint
- ONE-C control board comprising:** Power supply, PLC, frequency converter, SD card, RJ45 (Modbus) and torque limiter
- ONE-SENSE sensor:** Automatic motor management and control
- Available for:** LBA 6, LBA 63 PK, LBA 63 PG



PAID PARKING INDUSTRY SERVICES



DATE OF UPDATE: 02/07/2025

For more information, contact our teams on **+33 (0)4 78 86 02 86** or at contact@onlylba.com or go to www.onlylba.com

