

URBICANDE necklace bollard

W&I WILMOTTE & INDUSTRIES

**URBICANDE NECKLACE BOLLARD,
STYLISH AND WITHSTANDS THE IMPACT OF AN HGV
OF UP TO 12 TONNES AT 80 KM/H**
H 60 CM/100 CM - Ø25 CM



Integrates into the urban landscape, protects without causing alarm

Bollard impact resistance certified through crash tests and compliant with standards

Customisable: bollard head, height and combinations

Various potential combinations

STANDARD CHARACTERISTICS

• Cylinder:

- Steel cylinder Ø 25 cm - height 60/100 cm
- Impact resistance defined by the chosen bollard model
- Cast iron collar
- Adjustment feet



MADE IN FRANCE



URBICANDE necklace bollard

TECHNICAL SPECIFICATIONS

Paint / Finish	RAL steel colour and bamboo bench
Dimensions	Ø 25 - H 60 or 100 cm steel

OPTIONAL FEATURES

Customisation

- Choice of RAL colours

CERTIFICATION

BOLLARDS	HEIGHT		IMPACT RESISTANCE - CRASH TESTED					
	60 cm	100 cm	1.5 t at 48 km/h	3.5 t at 48 km/h	7.2/7.5 t at 48 km/h	7.5 t at 64 km/h	7.2/7.5 t at 80 km/h	12 t at 80 km/h
F25-60 1548/TFP	•		•					
F25-60 3548/TFP	•			•				
F25-60 7548/TFP	•				•			
F25-60-C80/FP	•				•			
F25-100 7548/TFP		•			•			
F25-100 7564		•				•		
F25-100-C80/FP		•					•	
F25-100 7580		•					•	
F25-100 12080		•						•

Conventional sealing from 500 mm to 1,000 mm depth

FP: 250 to 500 mm

TFP: < 250 mm

VERSIONS

CHAINS



BENCHES



PLANTER

