



## STATIC POWER SUPPLY BOLLARD: WATER, ELECTRICITY, COMPRESSED AIR, ETC. UP TO EIGHT 230-V SOCKETS



Height: 120 cm  
Diameter: 22 cm

High strength steel  
bollard

Custom  
configurations

Choice of RAL  
colours

NFC 17-200 &  
NFC 15-100-compliant

### STANDARD CHARACTERISTICS

- Static power supply bollard, static above ground
- **Cylinder:**
  - Steel bollard thickness 4 mm, Ø 220 mm
  - Height above ground 1,200 mm
  - Anti-corrosion treatment by 40 micron zinc coating + epoxy powder 30 to 40 microns
  - Equipped with 2 doors locked by security locks
  - Supplied with 2 keys
- **Plate:**
  - On 400 x 400 mm plate
  - Supplied with a sealing template
  - Electrical equipment integrated on stainless steel plate
  - Differential circuit breakers integrated under IP44 window
- Compliant with the NFC 17-200 / NFC 15-100 standard
- Main disconnection by 63 or 125 A / 400 V disconnect switch



MADE IN FRANCE

## TECHNICAL SPECIFICATION

Power supply	400 V
Paint / Finish	RAL 7016 / 250°C polyester powder coating
Dimensions (H-Ø)	1,200 x 220 mm
IP components	IP 44

## OPTIONAL FEATURES

- Special colour paint on RAL base
- Customisable electrical equipment
- Water tap integration
- Electric meter on sockets
- Low current
- Exogel system

## INSTALLATION

