



STATIC POWER SUPPLY BOLLARD: WATER, ELECTRICITY, COMPRESSED AIR, ETC. UP TO 12 230-V SOCKETS



Height: 126 cm
Diameter: 32 cm

High strength
steel bollard

Custom
configurations

Choice of RAL
colours

**NFC 17-200 &
NFC 15-100-compliant**

Cable guide for
use in the closed
position

STANDARD CHARACTERISTICS

- Static power supply bollard, static above ground
- **Cylinder:**
 - Steel bollard thickness 4 mm, Ø 320 mm
 - Height above ground 1270 mm
 - Anti-corrosion treatment by zinc coating 40 microns + epoxy powder 30 to 40 microns
 - Equipped with 2 doors locked by security locks
 - Supplied with 2 keys
 - Cable bushing for closed use
- **Plate:**
 - On 360 x 360mm plate
 - Supplied with a sealing template
 - Electrical equipment integrated on stainless steel plate
 - Differential circuit breakers integrated under IP44 window
- Compliant with the NFC 17-200 / NFC 15-100 standard
- Main disconnection by 63 or 125 A / 400 V disconnect switch



TECHNICAL SPECIFICATION

Power supply	400 V
Paint / Finish	RAL 7016 / 250°C polyester powder coating
Dimensions (H-Ø)	1,270 x 320 mm
IP components	IP 44

OPTIONAL FEATURES

- Special colour paint on RAL base
- Customisable electrical equipment
- Water tap integration
- Electric meter on sockets
- Low current
- Exogel system

INSTALLATION

