

>> F25-100-7548

**STATIC SECURITY BOLLARD -
WITHSTANDS THE IMPACT OF A 7.5-TONNE HGV AT 48 KM/H
H100 CM - Ø25 CM**



Multiple Finishes available (RAL, stainless steel, lighting)

8 cm gap above Foundation for floor finish

Bollard intact after crash test

Customisable

Optimised sealing in a 49 cm deep ground beam

STANDARD CHARACTERISTICS

• Cylinder:

- Steel version:
 - Steel cylinder treated by cataphoresis and epoxy powder coating Ø 25 cm - height 100 cm with removable flat top to be sealed
 - Finished with a 4 mm thick steel disc to be sealed on the top of the bollard
- Stainless steel version:
 - Hot-dip galvanised steel cylinder with stainless steel shell sleeve, microblasted finish Ø 25 cm - height 100 cm
 - Slinging device integrated into the bollard



TECHNICAL SPECIFICATION

Resistance	640,000 J
Paint / Finish	RAL 7016 steel colour
Cylinder dimensions (H-Ø)	1,000 mm / 250 mm

CERTIFICATION

Resistance certified by crash test and with bollard intact after impact:



7.2 tonnes at 48 km/h

OPTIONAL FEATURES

- Microblasted stainless steel sleeve
- Adjustment feet
- Retroreflective tape
- Brushed stainless steel finish gr 220
- Paint with seafront treatment
- Light strip
- Customised sleeve

INSTALLATION

