

> F25-60C80 FP

STATIC SECURITY BOLLARD

WITHSTANDS THE IMPACT OF A 7.5-TONNE HGV AT 48 KM/H

H60 CM - Ø25 CM



Multiple Finishes
available (RAL,
stainless steel)

**8 cm gap above
Foundation for
Floor Finish**

Bollard intact
after crash test

Customisable

Resistant
and discreet

STANDARD CHARACTERISTICS

• Cylinder:

- Hot-dip galvanised steel Ø 25 cm - height 60 cm
- Microblasted stainless steel shell sleeve



F25-60C80 FP

TECHNICAL SPECIFICATION

Resistance	666,000 J
Cylinder dimensions (H-Ø)	250 / 600 mm
Paint / Finish	Stainless steel sleeve

CERTIFICATION

Resistance certified by crash test with bollard intact after impact:



1.75 tonnes at 80 km/h



Supplemented by a digital crash test:
7.5 tonnes at 48 km/h

OPTIONAL FEATURES

- Adjustable foot device for laying on concrete slab
- Choice of RAL colours
- Customised sleeve
- Stainless steel sleeve
- Retroreflective tape
- Brushed stainless steel finish
- Microblasted stainless steel finish
- Light strip integrated into the bollard

INSTALLATION

