



MANUAL SECURITY BARRIER - WITHSTANDS THE IMPACT OF A 7.2-TONNE HGV AT 80 KM/H LENGTH 2 TO 10 M



Low and simplified
maintenance

Installation and
sealing in 24 hours

**High security level
without a power supply**

Effortless opening
in both directions
of travel

Designed
for regular
operation

STANDARD CHARACTERISTICS

- **Arm:** Steel 120 x 120 mm
- **Posts:** Very thick steel Ø 250 mm
- **Treatment:**
 - Arm: galvanised steel and thermo-lacquering
 - Posts: zinc plating and thermo-lacquering
- **Opening:** In both traffic directions 180°
- **Locking:** Lockable in closed position
- **Bracing:** From 7 m



TECHNICAL SPECIFICATIONS

Resistance	1,777,000 J
Paint	RAL 7016 polyurethane paint
Widths	From 2 to 10 m
Lock	Closing pin

CERTIFICATION

Impact resistance certified by crash test:



7.2 tonnes at 80 km/h
Tested in a shallow version



Complemented by a digital crash test with a 30-tonne HGV at 48 km/h

OPTIONAL FEATURES

Customisation

- Polyester paint (RAL choice)
- Two-tone posts / arm
- Position contact
- Lockable locking pin
- Reflective strip

INSTALLATION

